

# BAYESIAN WEIGHT UPDATES STABILIZE AND IMPROVE LOCAL LEARNING IN A RECURRENT NEURAL NETWORK

Jorge A. Menéndez<sup>1,2</sup> & Peter E. Latham<sup>1</sup>

<sup>1</sup> Gatsby Computational Neuroscience Unit, <sup>2</sup> Centre for Computation, Mathematics and Physics in the Life Sciences and Experimental Biology, University College London



## The Problem: local learning in the brain

How can a synapse know how to set its strength without knowing the others'?

**solution:** given the information locally available, estimate the strengths of the others and use this to estimate your own

► **Hypothesis:** synapses optimally integrate estimates of the others' weights to infer their own


$$w_i(t+1) = \arg \max_w \log P(w_i^* = w | \underbrace{\mathcal{D}_i(t)}_{\text{locally available data}})$$

$$\approx w_i(t) + \underbrace{\sigma_i^2(t)}_{\text{learning rate}} \mathcal{L}'_{i,t}(w_i(t))$$

**learning rate  $\propto$  uncertainty**

Q. How can this improve learning in a recurrent network?

## Setup: reservoir computing



► Gaussian posterior yields simple learning rule:

$$w_i(t) = w_i(t-1) + \alpha_i(t) \delta(t) \phi(x_i(t))$$

$$\alpha_i(t) = \frac{\sigma_i^2(t)}{\sigma_\ell^2} = \frac{1}{\frac{\sigma_\ell^2(0)}{\sigma_i^2(0)} + \sum_{t'=1}^t \phi(x_i(t'))^2}$$

► every synapse has access to global supervisory error signal

$$\mathcal{D}_i(t) = \{\phi(x_i(t')), w_i(t'), \delta(t')\}_{t'=1}^t, \quad \delta(t) = z^*(t) - z(t)$$

► synapse  $i$ 's model of other synapses:

$$\forall j \neq i, \quad \mathbb{E}[w_j^* - w_j] = 0, \quad \text{Var}[w_j^* - w_j] = \sigma_\ell^2/N$$


► this implies Gaussian likelihood:

$$\delta(t) = (w_i^* - w_i)\phi(x_i) + \underbrace{\sum_{j \neq i} (w_j^* - w_j)\phi(x_j)}_{\rightarrow \mathcal{N}(0, \sigma_\ell^2)}$$


$$P(w_i^* = w | \mathcal{D}_i(t)) \propto P(\delta(t) | w_i^* = w, w_i(t), \phi(x_i(t))) \times P(w_i^* = w | \mathcal{D}_i(t-1))$$

} a delta rule with **synapse-specific** and **time-varying** learning rate

## Faster learning



## Improved 'generalization'



## Conclusions

We find that a normatively derived learning rule implies a particular adaptive learning rate that improves stability of readout weights for reservoir computing.

The **Bayesian plasticity hypothesis** provides a general framework for formalizing normative principles of synaptic plasticity

- extension to Dale's law<sup>1</sup>
- learning recurrent weights<sup>2</sup>
- spike-based learning rules<sup>3</sup>
- heterosynaptic plasticity
- dendritic branching

## References

1. Aitchison, L., Pouget, A., & Latham, P. E. (2014). Probabilistic Synapses. *arXiv preprint arXiv:1410.1029*.
2. Miconi, T. (2017). Biologically plausible learning in recurrent neural networks reproduces neural dynamics observed during cognitive tasks. *Elife*, 6.
3. Pfister, J. P., Toyoizumi, T., Barber, D., & Gerstner, W. (2006). Optimal spike-timing-dependent plasticity for precise action potential firing in supervised learning. *Neural computation*, 18(6), 1318-1348.